

DEC-KING®

EXTERIOR WOOD SCREWS


Corrosion resistant fasteners for exterior wood applications



PRODUCT FEATURES

- Coated with Climacoat® for maximum resistance to corrosion, staining and streaking inside the lumber and on the deck.
- Recommended for ACQ treated wood.
- Pullout strength is superior over nails.
- Eliminates wood splitting, nail pops, hammer marks, and bent nails.
- Available in both #2 Phillips & #2 Square Drive.

SELECTOR GUIDE



| PART NO. | DESCRIPTION | HEAD STYLE | BOX QTY | APPLICATIONS |
|----------|-------------|-----------------|---------|---|
| 2176500 | 6 x 1-1/4" | #2 Phillips | 8,000 | 1" x 4" or 1" x 6" Base Trim; Lattice |
| 2136500 | 6 x 1-5/8" | #2 Phillips | 5,000 | 1" x 4" or 1" x 6" Base Trim; Balusters; Lattice |
| 2138500 | 7 x 2" | #2 Phillips | 3,500 | 5/4" x 4" or 5/4" x 6" Radius Edged Decking; 1" x 4" or 1" x 6" Base Trim; Ballisters; Lattice |
| 2180500 | 8 x 2-1/2" | #2 Square Drive | 2,500 | 5/4" x 4" or 5/4" x 6" Radius Edged Decking; 2" x 4" or 2" x 6" Decking; 2" x 6" or 2" x 8" Rail Cap or Base Trim |
| 2140500 | 8 x 2-1/2" | #2 Phillips | 2,500 | |
| 2181500 | 8 x 3" | #2 Square Drive | 2,000 | 2" x 4" or 2" x 6" Decking; 2" x 6"; 2" x 8" Rail Cap or Base Trim |
| 2141500 | 8 x 3" | #2 Phillips | 2,000 | |
| 2142500 | 10 x 3-1/2" | #2 Phillips | 1,000 | |

PERFORMANCE DATA

| PULLOUT VALUES IN WOOD (AVERAGE LBS. ULTIMATE) | | | | |
|--|---|------|-----|--------|
| DESCRIPTION | EMBEDMENT IN 2 X 4 STUD GRADE S.Y. PINE | | | |
| | 1/2" | 3/4" | 1" | 1-1/4" |
| 6 x 1-1/4" | 182 | 329 | 422 | - |
| 6 x 1-5/8" | 182 | 329 | 422 | 620 |
| 7 x 2" | 189 | 318 | 440 | 630 |
| 8 x 2-1/2" | 186 | 290 | 502 | 630 |
| 8 x 3" | 186 | 290 | 502 | 645 |
| 10 x 3-1/2" | 241 | 386 | 522 | 721 |

The values listed are ultimate averages achieved under laboratory conditions and apply to Buildex manufactured fasteners only. Appropriate safety factors should be applied to these values for design purposes.

HEAD STYLES

